

IFP A10VSO PISTON PUMP ORDERING CODE



IFP A10VSO ORDERING CODE

SAMPLE CODE:	IFP	A10V	S	O	28	DR	/	31	R	P	S	C	62	NOO
Legend	(1)	(2)	(3)	(4)	(5)	(6)		(7)	(8)	(9)	(10)	(11)	(12)	(13)
(1)	IFP - INTERNATIONAL FLUID POWER PRODUCTION													
(2)	A10V - HIGH PRESSURE / VARIABLE VOLUME AXIAL PISTON PUMP													
(3)	S - MAXIMUM VOLUME STOP													
(4)	O - OPEN LOOP													
(5)	FRAME SIZE - 18 / 28 / 45 / 71 / 100 / 140													
(6)	PUMP CONTROL: (DR) PRESSURE CONTROL (DRG) REMOTE CONTROL (DG) TWO POINT, DIRECT CONTROL (DFR) PRESSURE & FLOW CONTROL (DFR1) PRESSURE AND FLOW CONTROL (ORIFICE X CHANNEL CLOSED) (DFLR) PRESSURE, FLOW AND TORQUE CONTROL													
(7)	31 - DESIGN													
(8)	ROTATION: (R) C.W./RIGHT HAND (L) C.C.W./LEFT HAND													
(9)	SEALS: (P) Nitril / (V) Viton													
(10)	SHAFTS: (P) - METRIC PARALLEL WITH KEY (S) - SAE-SPLINE (K) - SAE- PARALLEL WITH KEY (U) - SAE SPLINE / REDUCED DIAMETER													
(11)	MOUNTING FLANGE: (C) - SAE 2 HOLE (size 18 - 100) (D) - SAE 4 HOLE (size 140)													
(12)	PORTING: (61) - SAE FLANGE REAR CONNECTIONS / UNC BOLTS (62) - SAE FLANGE SIDE CONNECTIONS / UNC BOLTS (11) - SAE FLANGE REAR CONNECTIONS / METRIC BOLTS (12) - SAE FLANGE SIDE CONNECTIONS / METRIC BOLTS <i>Note: Code 61/11 can only be used with NOO STANDARD COVER - Not with through drive</i>													
(13)	OPTIONAL THROUGH DRIVE: (NOO) - STANDARD COVER/NO THROUGH DRIVE ** OPTIONAL THROUGH DRIVES ** (K01) - SAE-A MOUNT / SAE-A COUPLING (Sizes 18-140) (K52) - SAE-A MOUNT / SAE-B COUPLING (Sizes 18-140) (K68) - SAE-B MOUNT / SAE-B COUPLING (Sizes 28-140) (K04) - SAE-B MOUNT / SAE-BB COUPLING (Sizes 45-100) (K07) - SAE-C MOUNT / SAE-C COUPLING (Sizes 71-140) (K24) - SAE-C MOUNT / SAE-CC COUPLING (Sizes 100-140) (K17) - SAE-D MOUNT / SAE-D COUPLING (Sizes 140)													